





ever Joy ever Triumph

Worldwide

Product

- **EJ-KVM108IP**
- **EJ-KVM116IP**

Specification			
Model	KVM over IP-8 PORT	KVM over IP-16 PORT	KVM over IP-32 PORT
PC Port	8	16	32
Console Port	1	1	1
PC Port Connector (All Female Types)	PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15 pin		
Console Port Connector (All Female Types)	Local Console: PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15pin Remote Console: RJ-45 8P8C		
Serial Port (DB9 pin Male)	1	1	1
LAN port (RJ-45 8P8C)	1 10BASE-T Ethernet uses Category 3/4/5/5E/6 UTP 100BASE-T Ethernet uses Category 5/5E/6 UTP		
Reset button	Press Button Bank plus Button 8 on front panel	Press Button Bank plus Button 8/16 on front panel	
Keyboard Emulation	PS/2		
Mouse Emulation	PS/2		
VGA Resolution	Local : 1600 X1200 Remote : 1280 X1024		
Housing	Metal		
Power Adapter	DC 5V, 2.5A		
Operation Temperature	0~50°C		
Storage Temperature	-20~60°C		
Humidity	0~80%, Non-Condensing		
Size	Rackmount size		
Weight (kg)	3500g	4000g	4500g
Dimension (mm)	429.6(W)X214(L)X45.2(H)	429.6(W)X214(L)X45.2(H)	429.6(W)X214(L)X88(H)
<b>System requirement</b>			
Local console side	One PS/2 Keyboard, one PS/2 Mouse and one monitor		
Remote Console side	One PC or Multiple PCs are linked into the network		
Computer side	One PC or Server or the console port of KVM switch unit		