



AC Input:

- > Input Voltage 110V/230V
- > Efficiency >68% @ full load ,nominal line
- > Input Current 9A/5A max
- > Inrush Current 80A max @230Vac 25°C cold start
- > Input Frequency 47~63 Hz
- > Leakage Current 3.5mA max.

DC Output:

Output	Voltage	Regulation	Min .Load	Max .Load	Ripple
V1	+5V	±5%	0.5A	32.0A	50mV
V2	+12V1	±5%	1.0A	14.0A	100mV
V3	+12V2	±5%	1.0A	15.0A	100mV
V4	3.3V	±5%	0.5A	22.0A	50mV
V5	-12V	±10%	0.0A	0.3A	150mV
V6	+5VSB	±5%	0.0A	2.0A	50mV

Features...

400W 6 Output, AC Input design

- > Operating temperature range from 0°C to 50°C
- > Build in DC remote ON/OFF , PG/PF TTL signal
- > Build in a 12cm Sleeve fan
- > Compiles with FCC Class B,CISPR Pub. 22,
EN55022 Class B, and CE requirements
- > UL/cUL E222785, TUV and CB EN 60950 certified
- > MTBF 100KHRs @ 25°C per MIL- HDBK-217F
- > 2 years manufacturer warranty