

**AC Input:**

- Input Voltage 110V/230V
- Efficiency >68% @ full load ,nominal line
- Input Current 9A/5A max
- Inrush Current 80A max @230Vac 25°C cold start
- Input Frequency 47~63 Hz
- Leakage Current 3.5mA max.

DC Output:

Output	Voltage	Regulation	Min .Load	Max .Load	Ripple
V1	+5V	±5%	0.5A	26.0A	50mV
V2	+12V1	±5%	1.0A	8.0A	100mV
V3	+12V2	±5%	1.0A	14.0A	100mV
V4	+3.3V	±5%	0.5A	20.0A	50mV
V5	-12V	±10%	0.0A	0.3A	150mV
V6	+5VSB	±5%	0.0A	2.0A	50mV

Features...

300W 6 Output, AC Input design

- Operating temperature range from 0°C to 50°C
- Build in DC remote ON/OFF , PG/PF TTL signal
- Build in a 12cm Sleeve fan
- Compiles with FCC Class B,CISPR Pub. 22, EN55022 Class B, and CE requirements
- UL/cUL E222785, TUV and CB EN 60950 certified
- MTBF 100KHRs @ 25°C per MIL- HDBK-217F
- 2 years manufacturer warranty

Connectors

- 20 + 4 Pins Motherboard Connectors
- 1 x SATA